

Laligurans Municipality

Office of Municipal Executive

Basantapur, Terhathum

Date: 2082/04/26

Instruction and Recommendation for CC Camera Installation with Accessories/Supported Devices.

The equipment specifications are mentioned below. The provided equipment/items should comply with or exceed the specifications listed below.

For Free CC Camera with Accessories/Supported Devices and Equipment.

S.N.	Equipment/Items	Specification Requirement	Remarks
1.	IP Camera 4MP Color	 Metal/Plastic Housing 4MP, 2688X1520 Resolution S+265/H.265/H.264 Min. illumination Color: 0.02Lux@F1.6 2 Warm lights, 15m Smart IR, IR Range: 50m Built-in Mic Support tripwire and perimeter POE, IP67 Warranty 1 Years 	
2.	IP Camera 4MP Full Color	 1/2.9" CMOS image sensor, low luminance, and high-definition image. 4 MP, 2688× 1520 Resolution H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light and the illumination distance is 50 m. ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection. Alarm: 2 in, 2 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built in Mic. IP67 protection, SMD Plus. Warranty 1 Years 	

3.	Gigabit SFP	 Single mode single core, 20 KM, SC Optical Port, 10/100/1000M adaptive with support for automatic inversion of MDI/MDIX. Warrantee: 1 years
4.	PoE + SFP Switch (4+2) Port	 4 x 1000 Mbps PoE Ports 1 x 1000 Mbps Uplink Port 2 x 2500Mbps SFP Port 65-Watt Power Input 130 Mtr. transmission distance 4 x 1000 Mbps PoE Ports,2 x 1000Mbps SFP Port Warranty 1 Years
5.	SFP Switch 6 Port	 6 Port SFP 3 Gigabit Ethernet (Bandwidth upto 18 Gbps) SC Optical Port, AC 90V240V or PoE Power Input, Total 30W Power, 6KV Lightning & 8KVESD Protection Metal body for quickly dissipate heat Warranty 1 Years
6.	Gigabit Ethernet Switch	 8 Port Gigabit Unmanaged Desktop Switch 8 x 10/100/1000 Mbps ethernet ports Store-and-forward switching Supports MAC address auto-learning and aging Warranty 1 Years
7.	NVR 10 Channel	 Up to 10-ch IP camera accesses Incoming/Outgoing bandwidth: 60Mbps/40Mbps S+265, H.265, S+264, H.264 video formats Decoding capability: 6MP (30fps) ×1 or 1080P(30fps) ×4 10-ch synchronous playback Up to 8 TB capacity for each HDD Simultaneous HDMI and VGA outputs Warranty 1 Years
8.	Monitor	 22 Inch , Refresh Rate 100Hz, Full HD IPS Panel Borderless Warranty 1 Years
9.	Hard Disk Drive 4 TB	 4 TB HDD Surveillance Internal Hard Disk Drive Min. 5200 RPM SATA for CCTV Camera Unparalleled data protection RV sensors built in ATA streaming support Warranty 2 Years
10.	Hard Disk Drive 6 TB	 6 TB HDD Surveillance Internal Hard Disk Drive Min.5200 RPM SATA for CCTV Camera Unparalleled data protection RV sensors built in ATA streaming support Warranty 2 Years

_	I .	
11.	Outdoor CAT 6 Cable	 Full Length 305 m CAT6 Solid Copper network cable Core diameter: 0.55mm Excellent transmission performance using solid copper Guaranteed long PoE transmission distance Great PVC
12.	CC Camera	CCTV Weatherproof Outdoor Camera Junction PVC box
	Outdoor Box	Enclosure IP65 Terminal Cable
13.	Pole Box Outdoor	 Basic frame: Metal Sheet with Paint/Fiber Sheet Bottom cover: cable entry cut-outs Front Door: Screw Lock/Key Lock
14.	Optical Fiber	• 6 Cores
	Cable	Single Mode, FRB
15.	Electrical Power	Concentric Cable
	Cable	• 10mm ²
16.	Ethernet Patch	D-Link CAT6 RJ45 Patch Chord ensure universal
	Cables	connectivity.
17		Min 1 Meters Long Divide for Outdoor Cat Cathornat calls
17.	RJ 45	D-Link for Outdoor Cat6 Ethernet cable.
18.	Optical Fiber	Core/Cladding: 9/125 Single Mode
	Patch Chord Cable	2 meters long
19.	Multiplug	Min. 3 port with 3 pins
		Copper Conductor
20.	Miniature Circuit	Rated Current 10 Amp.
	Breaker (MCB)	Double Pole
21.	Optical Fiber Joint	High quality plastics compact and lite weight. Easy to install
	Tiffin Box	Designed to be an outdoor usage.